

## CR-2 Stainless Steel Two Section Repair Clamps

Material Specifications	Bolts	304 stainless steel, 5/8” roll NC thread.
	Bolt & Receiver Bars	304 stainless steel. TIG welded to shell to form a strong fusion and fully passivated.
	Shell	304 stainless steel.
	Locking Washer Plate	304 stainless steel. Locks into position for easy tightening of nuts.
	Nuts	304 stainless steel & fluorokote coating.
	Washer	304 stainless steel and nylon washers are used to reduce wear on washer plate.
	Gasket	SBR Rubber -ASTM D 2000 AA4 15 Rubber is especially formulated for water service and has antioxidant, antiozonant agents to increase shelf life.
	Armour	304 stainless steel, heavy gauge, molded into gasket to prevent “hanging up” during installation.

Pipe Diameter	Catalogue Number	O.D. Range	08” Long	12” Long	16” Long	24” Long
			Length and approx. shipping weight lbs.			
4	CR2-Length0450	4.40-5.20				
4	CR2-Length0480	4.70-5.57	13	18	26	39
6	CR2-Length0663	6.50-7.30	14	21	28	44
6	CR2-Length0690	6.80-7.60	15	23	29	46
8	CR2-Length0863	8.50-9.30	17	25	30	48
8	CR2-Length0905	8.95-9.75	17	25	31	48
10	CR2-Length1110	11.00-11.80	n/a	27	33	50
10	CR2-Length1140	11.40-12.20	n/a	28	35	51
12	CR2-Length1275	12.65-13.45	n/a	29	36	52
12	CR2-Length1320	13.10-13.90	n/a	30	37	53
12	CR2-Length1385	13.85-14.65	n/a	32	40	57
14	CR2-Length1507	15.05-15.85	n/a	34	42	59
16	CR2-Length1715	17.15-17.95	n/a	n/a	44	65

\*Other ranges are available.

\*To order select, model (CR2), the length of clamp from the list above, and the model number from the list above. eg (CR2-080450)

\*All stainless material fully passivated.

\*Torque bolts to 60 FT. LBS

## CR-2 Stainless Steel Two Section Repair Clamps

List Price Per Clamp	Nominal Pipe Size	Catalogue Number	O.D. Range	08" Long	12" Long	16" Long	24" Long
	4	CR2-Length0450	4.40-5.20	166.28	258.88	349.03	523.07
	4	CR2-Length0480	4.70-5.57	166.28	258.88	349.03	523.07
	6	CR2-Length0663	6.50-7.30	176.98	279.30	369.17	550.24
	6	CR2-Length0690	6.80-7.60	176.98	279.30	369.17	550.24
	8	CR2-Length0863	8.50-9.30	194.94	301.94	399.12	588.19
	8	CR2-Length0905	8.95-9.75	194.94	301.94	399.12	588.19
	10	CR2-Length1075	10.65-11.45	214.49	362.20	434.83	701.64
	10	CR2-Length1110	11.00-11.80	214.49	362.20	434.83	701.64
	10	CR2-Length1140	11.40-12.20	214.49	362.20	434.83	701.64
	12	CR2-Length1275	12.65-13.45	253.09	379.93	491.33	744.47
	12	CR2-Length1320	13.10-13.90	253.09	379.93	491.33	744.47
	12	CR2-Length1360	13.60-14.40	253.09	379.93	491.33	744.47
	12	CR2-Length1385	13.85-14.65	327.59	425.76	536.05	804.15
	12-14	CR2-Length1438	14.35-15.15	327.59	425.76	536.05	804.15
	14	CR2-Length1507	15.05-15.85	327.59	425.76	536.05	804.15
	16	CR2-Length1592	15.90-16.75	327.59	425.76	536.05	804.15
	16	CR2-Length1656	16.55-17.35	389.69	468.21	601.82	853.65
	16	CR2-Length1715	17.15-17.95	389.69	468.21	601.82	853.65
	18	CR2-Length1782	17.80-18.60	408.10	509.36	633.66	966.57
18	CR2-Length1846	18.45-19.25	408.10	509.36	633.66	966.57	
18	CR2-Length1923	19.20-19.95	432.65	526.96	664.26	1005.78	
20	CR2-Length1990	19.90-20.70	432.65	526.96	664.26	1005.78	
20	CR2-Length2070	20.70-21.50	462.19	578.00	707.54	1068.36	
20	CR2-Length2152	21.50-22.30	462.19	578.00	707.54	1068.36	
22	CR2-Length2212	22.10-22.90	485.58	644.86	759.69	1145.03	
22	CR2-Length2290	22.90-23.70	485.58	644.86	759.69	1145.03	