

## CR-3 Stainless Steel Three Section Repair Clamps

Material Specifications	Bolts	304 stainless steel, 5/8” roll NC thread.
	Bolt & Receiver Bars	304 stainless steel. TIG welded to shell to form a strong fusion and fully passivated.
	Shell	304 stainless steel.
	Locking Washer Plate	304 stainless steel. Locks into position for easy tightening of nuts.
	Nuts	304 stainless steel & fluorokote coating.
	Washer	304 stainless steel and nylon washers are used to reduce wear on washer plate.
	Gasket	SBR Rubber -ASTM D 2000 AA4 15 Rubber is especially formulated for water service and has antioxidant, antiozonant agents to increase shelf life.
	Armour	304 stainless steel, heavy gauge, molded into gasket to prevent “hanging up” during installation.

Nominal Pipe Size	Catalogue Number	O.D. Range	08” Long	12” Long	16” Long	24” Long
12-14	CR3-Length1430	13.10-14.30	286.44	436.27	561.13	857.61
12-14	CR3-Length1485	13.65-14.85	286.44	436.27	561.13	857.61
14-16	CR3-Length1605	14.85-16.05	350.73	480.33	604.15	915.94
16	CR3-Length1712	15.92-17.12	350.73	480.33	604.15	915.94
16	CR3-Length1745	16.25-17.45	435.20	607.63	760.59	1154.36
18	CR3-Length1830	17.10-18.30	435.20	607.63	760.59	1154.36
18	CR3-Length1920	18.00-19.20	445.97	636.61	797.11	1154.36
18-20	CR3-Length2040	19.20-20.40	445.97	636.61	797.11	1154.36
20	CR3-Length2260	21.40-22.60	490.95	706.52	876.97	1354.24
22-24	CR3-Length2400	22.80-24.00	490.95	706.52	876.97	1354.24
24	CR3-Length2465	23.45-24.65	490.95	706.52	876.97	1354.24
24	CR3-Length2670	25.50-26.70	522.41	805.71	974.24	1434.89

\*To order select, model (CR3), the length of clamp from the list, and the model number from the list.  
eg, (CR3-122326)