

SC-2 Stainless Steel Service Saddle (Double Bolt)

Material Specifications

* SC-2 Stainless Steel Saddles are fully warranted for use on HDPE, (DR9, DR11, DR17), C-900, Asbestos Cement Pipe, SDR35 and IPS PVC pipe only, not for use on metal pipe.

Bolts	304 stainless steel, 5/8" roll NC thread.
Bolt & Receiver Bars	304 stainless steel. TIG welded to shell to form a strong fusion and fully passivated.
Shell	304 stainless steel.
Locking Washer Plate	304 stainless steel. Locks into position for easy tightening of nuts.
Nuts	304 stainless steel & fluorokote coating.
Washer	304 stainless steel washers are used to reduce wear on washer plate.
Gasket	SBR Rubber -ASTM D 2000 AA4 15 Rubber is especially formulated for water service.

1-¼", 1½" & 2" NPT & CC						1¼"- 1½" IP	2" IP	1¼"- 1½" CC	2" CC
Nom. Size in Inches	Catalogue Number	O.D. Range	Shell Wt.	Width in Inches	Weight each Lb.				
3	SC2-0350-TAP	3.40-3.70	20 gauge	5	3	115.23	n/a	1¼" - 138.31	n/a
4	SC2-0485-TAP	4.45-4.85	20 gauge	7½	3	115.23	129.26	138.31	148.55
4	SC2-0535-TAP	4.95-5.35	20 gauge	7½	3	119.06	133.10	142.15	152.38
6	SC2-0700-TAP	6.54-7.00	18 gauge	7½	5	124.14	138.31	147.44	157.65
6	SC2-0745-TAP	6.99-7.45	18 gauge	7½	5	127.99	142.15	151.28	161.49
8	SC2-0908-TAP	8.63-9.08	18 gauge	7½	6	132.33	146.40	155.63	165.82
8	SC2-0967-TAP	9.21-9.67	18 gauge	7½	6	136.16	150.23	159.47	172.72
10	SC2-1116-TAP	10.70-11.16	18 gauge	7½	6	144.09	154.37	163.67	173.76
10	SC2-1221-TAP	11.75-12.21	18 gauge	7½	6	147.93	158.22	167.51	177.59
12	SC2-1321-TAP	12.74-13.21	18 gauge	7½	7	147.97	161.95	171.19	181.35
12	SC2-1447-TAP	14.00-14.47	18 gauge	7½	7	151.82	165.78	175.03	185.18

* Torque bolts to 60 Ft. Lbs.

SC-2 Stainless Steel Service Saddle (Double Bolt)

Material Specifications

* SC-2 Stainless Steel Saddles are fully warranted for use on HDPE, (DR9, DR11, DR17), C-900, Asbestos Cement Pipe, SDR35 and IPS PVC pipe only, not for use on metal pipe.

Bolts	304 stainless steel, 5/8" roll NC thread.
Bolt & Receiver Bars	304 stainless steel. TIG welded to shell to form a strong fusion and fully passivated.
Shell	304 stainless steel.
Locking Washer Plate	304 stainless steel. Locks into position for easy tightening of nuts.
Nuts	304 stainless steel & fluorokote coating.
Washer	304 stainless steel washers are used to reduce wear on washer plate.
Gasket	SBR Rubber -ASTM D 2000 AA4 15 Rubber is especially formulated for water service.

¾" & 1" NPT & CC						¾" IP	1" IP	¾" CC	1" CC
Nom. Size in Inches	Catalogue Number	O.D. Range	Shell Wt.	Width in Inches	Weight each Lb.				
3	SC2-0350-TAP	3.40-3.70	20 gauge	5	3	77.48	82.80	85.61	90.36
4	SC2-0485-TAP	4.45-4.85	20 gauge	5	3	76.41	81.31	84.97	89.23
4	SC2-0535-TAP	4.95-5.35	20 gauge	5	3	79.48	84.38	88.04	92.30
6	SC2-0700-TAP	6.54-7.00	20 gauge	5	5	82.16	87.76	91.29	95.58
6	SC2-0745-TAP	6.99-7.45	20 gauge	5	5	85.23	90.83	94.36	98.65
8	SC2-0908-TAP	8.63-9.08	20 gauge	5	6	91.41	93.59	94.64	98.99
8	SC2-0967-TAP	9.21-9.67	20 gauge	5	6	94.48	96.66	97.70	102.06
10	SC2-1116-TAP	10.70-11.16	18 gauge	5	6	105.28	109.69	113.23	117.60
10	SC2-1221-TAP	11.75-12.21	18 gauge	5	6	108.35	112.76	116.30	120.67
12	SC2-1321-TAP	12.74-13.21	18 gauge	5	7	110.56	115.37	118.90	123.29
12	SC2-1447-TAP	14.00-14.47	18 gauge	5	7	113.63	118.44	121.97	126.36

* Torque bolts to 60 Ft. Lbs.