

SC-4 Stainless Steel Saddle Clamp (Four Bolt)

Material Specifications

Bolts	304 stainless steel, 5/8" roll NC thread.
Bolt & Receiver Bars	304 stainless steel. TIG welded to shell to form a strong fusion and fully passivated.
Shell	304 stainless steel.
Locking Washer Plate	304 stainless steel. Locks into position for easy tightening of nuts.
Nuts	304 stainless steel & fluorokote coating.
Washer	304 stainless steel and nylon washers are used to reduce wear on washer plate.
Gasket	SBR Rubber -ASTM D 2000 AA4 15 Rubber is especially formulated for water service.

¾" & 1" FMI & CC							
Nom. Size in Inches	Catalogue Number	O.D. Range	Shell Wt.	Width in Inches	Weight per Lb.	¾" -1" IP	¾" -1" CC
4	SC4-0535-Tap	4.45-5.35	20 gauge	5	5.0	133.85	136.93
6	SC4-0745-Tap	6.60-7.45	20 gauge	5	5.0	139.08	142.87
8	SC4-0943-Tap	8.60-9.43	20 gauge	5	5.5	143.68	148.05
8	SC4-0967-Tap	8.60-9.67	18 gauge	5	5.5	143.68	148.05
10	SC4-1116-Tap	10.70-11.16	18 gauge	5	6.5	158.03	161.40
10	SC4-1221-Tap	11.40-12.20	18 gauge	5	6.5	158.03	161.40
12	SC4-1321-Tap	12.70-13.30	18 gauge	5	7.0	164.16	167.62
12	SC4-1447-Tap	13.70-14.50	18 gauge	5	7.0	164.16	167.62
14	SC4-1530-Tap	15.25-16.05	18 gauge	5	9.0	167.54	172.37
16	SC4-1740-Tap	17.20-17.80	18 gauge	5	9.0	176.31	179.17
18	SC4-1950-Tap	19.40-20.00	18 gauge	5	10.0	179.66	182.98
20	SC4-2160-Tap	21.40-22.00	18 gauge	5	10.0	209.97	213.35
24	SC4-2400-Tap	23.80-24.40	18 gauge	5	12.0	224.08	227.55
24	SC4-2580-Tap	25.80-26.20	18 gauge	5	12.0	227.42	230.90

SC-4 Stainless Steel Saddle Clamp (Four Bolt)

Material Specifications

Bolts	304 stainless steel, 5/8" roll NC thread.
Bolt & Receiver Bars	304 stainless steel. TIG welded to shell to form a strong fusion and fully passivated.
Shell	304 stainless steel.
Locking Washer Plate	304 stainless steel. Locks into position for easy tightening of nuts.
Nuts	304 stainless steel & fluorokote coating.
Washer	304 stainless steel and nylon washers are used to reduce wear on washer plate.
Gasket	SBR Rubber -ASTM D 2000 AA4 15 Rubber is especially formulated for water service.

1-1/4" & 2" NPT & CC							
Nom. Size in Inches	Catalogue Number	O.D. Range	Shell Wt.	Width in Inches	Weight per Lb.	1-1/4" & 2" IP	1-1/4" & 2" CC
4	SC4-0535-Tap	4.45-5.35	20 gauge	7½	7.0	181.43	201.32
6	SC4-0745-Tap	6.60-7.45	20 gauge	7½	8.0	188.24	208.12
8	SC4-0943-Tap	8.60-9.43	20 gauge	7½	8.5	199.26	214.03
8	SC4-0967-Tap	8.60-9.67	18 gauge	7½	8.5	199.26	214.03
10	SC4-1116-Tap	10.70-11.16	18 gauge	7½	9.5	208.13	231.62
10	SC4-1221-Tap	11.40-12.20	18 gauge	7½	9.5	208.13	231.61
12	SC4-1321-Tap	12.70-13.30	18 gauge	7½	10.5	214.25	232.20
12	SC4-1447-Tap	13.70-14.50	18 gauge	7½	10.5	214.25	232.20
14	SC4-1530-Tap	15.25-16.05	18 gauge	7½	12.0	219.70	238.73
16	SC4-1740-Tap	17.20-17.80	18 gauge	7½	12.0	230.90	250.46
18	SC4-1950-Tap	19.40-20.00	18 gauge	7½	13.0	237.11	256.06
20	SC4-2160-Tap	21.40-22.00	18 gauge	7½	13.0	244.94	268.03
24	SC4-2400-Tap	23.80-24.40	18 gauge	7½	14.0	259.05	285.68
24	SC4-2580-Tap	25.80-26.20	18 gauge	7½	14.0	274.78	302.06